



PowerG + Wireless Repeater

Range Repeated, Batteries Boosted



48-Hour Battery Backup

Keeps the network running for up to 48 hours when AC power is not available.



Expanded Range

Further extends the best-in-class range of PowerG when placed on a network's edge.



Easy Installation

Enroll devices faster with QR codes.



Modern Aesthetic

New sleek design offers elegance and functionality without sacrificing security.



Over-The-Air Updates

Upgrade sensors and resolve device issues remotely.



Battery Life Reporting

Monitor the exact battery percentage of all devices.



PowerG+

DSC



SPECIFICATIONS

Frequency Band	912 to 919 MHz	
Communication Protocol	PowerG +	
Power Supply	100-240 VAC to 6V/1A DC For UL Listed product, 120 VAC, 60 Hz. Sure-Power type SW-060100A.	
Battery Type	Rechargeable. 3.6 V 2200 mAh Li-ion Q-LITE type ICR18650. For UL Listed product, Q-LITE type ICR18650.	
Backup Battery Duration	At least 48 hours, for UL listed product 24 hours	
Operating Temperature	0°C (32°F) to 49°C (120°F)	
Storage Temperature	-20°C (-4°F) to 60°C (140°F)	
Relative Humidity	Up to 93% non-condensing	
Dimensions (LxWxD)	180 mm x 180 mm x 48 mm (7.1 in. x 7.1 in. x 1.9 in.)	
Weight (including battery)	434 g (15 oz)	
Color	White	
Certifications	PGP9920	FCC (912 to 919 MHz): 47CFR part 15.247 ISED (912 to 919 MHz): RSS-247 UL/ULC: UL 2610, UL 1637, UL 1023, UL 985, ULC-S545, ULC-S304
Part Number	PGP9920 – NA and LATAM	



PowerG+

DSC

