

PI-25

Single Port 2.5 Gigabit 30W PoE/PoE+ Injector

OVERVIEW

The Single Port PoE+ (Power Over Ethernet) Injector delivers both data and electrical power to PoE enabled devices using standard Ethernet cable. This eliminates the need to place devices (i.e. wireless access points) near a power outlet, allowing for greater AV installation flexibility, while also reducing AV installation and labor costs. Power Cord included in this kit. Your Ethernet cable is required.



FEATURES

- IEEE 802.3af/at compliant
- Delivers up to 30 Watts of power
- Supports data rates up to 2.5Gbps
- Built in power supply

PRODUCT INFORMATION

PART #	DESCRIPTION	
PI-25	Single Port 2.5 Gigabit 30W PoE/PoE+ Injector	

SPECIFICATIONS

GENER	RAL SPECIFICATIONS
STANDARDS	IEEE 802.3 af/at compliant
OUTPUT VOLTAGE	54V (0.6A)
OUTPUT POWER	30W
INPUT VOLTAGE	AC100-240V 0.8A 50 60Hz
	10/100/1000Mbps 2.5Gbps
PORTS	1-Power Input
CABLE	Cat5e or better
	PoE: Indicates power is being passed to the Connected 802.3af/at PoE device
LEDS	PWR: Power is connected to the PoE Injector
DIMENSIONS	W x D x H: 2.3" (58.4mm) x 3.94" (100mm) x 1.31" (33.4mm)
WEIGHT	.55lbs (.25kg)
ENVIRONM	IENTAL SPECIFICATIONS
OPERATING TEMPERATURE	32°F to 104°F (0°C to 40°C)
STORAGE TEMPERATURE	22°F to 176°F (-30°C to 80°C)
OPERATING HUMIDITY	5% to 90% (Relative Humidity Non-Condensing)
STORAGE HUMIDITY	5% to 95% (Relative Humidity Non-Condensing)
LE	ED INDICATORS
Port/LED	Function
DWD LED	On: Power is connected to the PoE Injector
PWR LED	Off: Injector is not receiving power
DATA & PWR OUT	Delivers power and data (via Ethernet cable) to the connected PoE enabled device
DATA IN	Connects to your data source over Ethernet cable



PI-25

NOTES

 If the PWR LED does not illuminate, it indicates power may not be connected properly or the cable is loose or unplugged.

ADDITIONAL INFORMATION

FREE DESIGN SERVICE

Go to **legrandav.com/cap** to access free design services from Luxul network experts.

PACKAGE CONTENTS

- Luxul PI-25 Single Port 2.5 Gigabit 30W
 PoE/PoE+ Injector
- Power Cord

ORDERING INFORMATION

REGION	PART NUMBER
North America	PI-25
Europe	PI-25-E

LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

SIMPLY CONNECTED | legrandav.com

NORTH AMERICA 800.572.2011 & 801.822.5450 av.luxul.support@legrand.com

EMEA +31 495 580 840 av.emea.sales@legrand.com

©2025 Legrand AV Inc. 250238 Rev A 4/25 Luxul is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.