

FEATURING:

- All-new intuitive, wall-mounted touchscreen control of security system and/or optional video and smart home or business automation, with Z-Wave® locks, lights, temp & small appliances*
- Brilliant 7-inch high-res color 1024 x 600 TFT capacitive display
- Ultra-responsive, high-speed, quad-core processor
- Choice of hardwired or wireless iBridge Touch™ models, WiFi models with 12V plug-in transformer (supplied)
- Slimline, clean decor-friendly design and GUI; matches new iBridge App
- Built in voice prompts and sounder speaker
- Easy Icon Security Control &/or Matching Conventional Keypad Control of Napco Gemini and other leading brand panels; also arm/disarm control of any panel with a keyswitch input

SECURITY:

- Easy icon one-button control of Arm, Stay, Away etc.
- Also mirrors top brand keypads in conventional keypad mode, supports ADT®/Honeywell®, DSC®, Napco Gemini, etc.
- Can also be used with any brand control panel with keyswitch input for one-button arm/disarm
- Entry/Exit countdown displayed
- Three Emergency buttons
- Quickly and easily bypass zones

VIDEO:

- Multiview on-premises viewing of up to 6 cameras, with easy scroll and finger-spread zoom display
- Choice of iBridge Video™ Cameras (also supports original iSeeVideo Cameras). WAP-free; connectivity via either StarLink Connect® or IBR-ZREMOTE Module
- Video can be added as MMS notifications and event/scene triggers
- Easy camera enrollment

SMART AUTOMATION / IOT:

- Choice of smart automation IoT integration panel interface universal StarLink Connect Dual Path Communicator with Built-in Z-Wave Hub (-Z model). For use with any panel with keyswitch, automation scenes on arm/disarm. Or for Napco-only option: or Gemini hardwire or WiFi iBridge Z-Remote Panel Module
- Supports standard Z-Wave Devices for home or biz smart control and increases range performance up to 100%
- Create and control custom scenes, ideal for smart home or business, combining security, video and/or automation-controlled devices by touch, by trigger event or by schedule
- Dealer scene-creation auto-generates custom button for consumer use/ touch-activation



StarLink Connect* adds Universal Cell/IP, IoT Control*, SMS alerts & Keypad App for Top Brands (also keyswitch or Gemini Z-Remote options for connectivity)

NOTIFICATIONS:

- Onscreen notification viewing of SMS text or MMS multimedia notifications
- Also easy menu-driven ability for user to set or modify their own notifications by category, e.g., alarm event, business, family, pet care, elder care, vacation, etc.

DEALER EASE:

 Easy Setup Wizard & System Configuration with at-a-glance Full Account Info Screen





- Easiest WiFi connection (802.11) with automatic choose-a-network display & color-coded signal strength optimizer
- Add or delete User Codes
- Selectable Security-Only Mode (doesn't show unavailable options for applications currently without video or automation)
- Choose your Panel Brand's Conventional Keypad Style
 Even Do Keypad-Programming Your Way on Touchscreen:

Arm/Disarm icons or Mirrors keypad from popular brands, ADT®/Honeywell®, DSC®, Napco



- Easy firmware updates onscreen
- 4 Touchscreens supported per system
- Easy 3-Gang Box wall-mount installation (both models)
- Eligible product for iBridge Connected Home & Business Authorized Dealer Program

SPECIFICATIONS:

ELECTRICAL RATINGS

Speaker: 1 Integral 2WScreen on, idle: 300mA

Clicking menu items: 380mA

- Power: IBR-TOUCH-WL, powered by a supplied 12VDC adapter, wireless WiFi connectivity. (See details Touchscreen WI2296LF & StarLink Connect WI2193A)
- IBR-TOUCH, with hardwire security connectivity plus WiFi support for Z-Wave & video. (See details Touchscreen WI2296LF & StarLink Connect WI2193A)
- Four (4) Touchscreens supported per security system



FEATURES:

- CPU: Quad core processor, (up to 1.6GHz)
- Wi-Fi: 802.11b/g/n with integral antenna
- LCD Size: 7 inch digital screen
- **Resolution Ratio:** 1024 x 600 x, 16:9 aspect ratio, 16.7 million colors
- **Pixels:** 1024 x RGB (3) x 600
- Touch Screen: Digital and full-screen, capacitive
- OS: Android
- Smart automation/IoT integration panel interface options (where enabled): universal StarLink Connect Dual Path Communicator with Built-in Z-Wave Hub (-Z model) or Gemini hardwire or WiFi iBridge Z-Remote Panel Module
- Video: View up to 6 cameras, choice of new iBridge Video Cameras (No WAP) or iSee Video Cameras*
- Easy WiFi Connection: Choose-a-network display, shows available WiFi networks; color-coded onscreen signal strength optimizer indicates green (good), yellow (trouble) or red (no-go)

HOUSING:

- **Dimensions (HxWxD):** 5-3/8 x 7-7/8 x 7/8 in. (13.7 x 20 x 2.2 cm)
- Weight: 14.3oz (405g)
- Operating Temperature: 0-49°C (32-120°F)

ORDERING INFO:

- IBR-TOUCH-WL 1024 x 600 7" hi-res color touchscreen for security and optional automation or video control (using StarLink Connect or IBR-ZREMOTE), wireless connectivity, powered by 12VDC adapter, supplied.
- IBR-TOUCH similar to above, but with hardwire security connectivity plus WiFi support for Z-Wave & video (using StarLink Connect or IBR-ZREMOTE.)
- IBRIDGE APP New & Improved Matching Smart Device App for remote control, mirroring touchscreen look and operation including security icons and conventional keypad modes (top panels), for easy consumer use. Available on Google Play®or iTunes®

COMPLEMENTARY OPTIONS:

- SLE-CDMA-Z For IoT &/or Video Touchscreen support*,
 Universal Dual Path Cell/IP Communicator, Verizon Network
 Certified® CDMA, with Built-in Smart Hub with Z-Wave Control,
 Virtual Keypad App, SMS/MMS Notification and full keypad bus
 support of leading panel brands, Honeywell®/ADT®, DSC®, Napco
 or abridged support of any panel brand with keyswitch input.
- SLE-LTEV-Z as above but, Verizon Network Certified® LTE
- SLE-GSM-3/4G-Z as above, but on AT&T Network
- IBR-ZREMOTE Remote Service/Z-Wave Control Module for Gemini Expandable Panels, significantly expands Z-Wave device range (supports standardly available devices)
- IBR-ZREMOTE-W As above, but easy WiFi -connected model
- ISV2-CAM iBridge Video Camera, 2-way audio built in mic/ speaker and 32GB onboard video storage (up to 7 days HD video 720p). Professional grade, fast-connect, up to 20/30 fps 2.4GHz WiFi 802.11 b/g/n, 1.3MP (1280x960) CMOS High Def. Sensor.
- ISV2-PT iBridge Video Pan/Tilt Camera, WiFi Hi-Def. P/T Camera, true 2-way audio built in mic/speaker and 32GB onboard video storage (up to 7 days HD video 720p).
- ISV2-DOME iBridge Video Outdoor Dome Camera, Outdoor Dome Camera, WiFi Hi-Def. Indoor/Outdoor Dome Camera with POE option and 32GB onboard video storage (up to 7 days HD video 720p). Ingress & Vandal- Protected Weatherproof camera (IPI67, IK10).
- iBridge Touch Touchscreen Instruction Manual WI2296LF
- StarLink Connect Instruction Manual WI2193A