



// HD FINISHING SPECS

Designed for rack lacing and other exposed drops between devices, monitors, etc. Planet Waves HD Finishing Wire features a soft, flexible TPE jacket making it really easy to tie to rack lacing bars. It also has a clean, polished look to enhance the overall appearance of your and finished installation work.

- Made in USA
- Meets 75 ohm HD standard
- Sweep-tested 3GHz over 100ft with nominal db loss
- Nominal Capacitance 18.2 pF/ft
- Premium oxygen-free copper
- 100% shielding with 95% tinned copper braid & tin foil shield
- Nitrogen-gas-injected foam PE dielectric
- TPE Jacket
- CM & CL2 rated for in-wall installations
- Max Pulling Tension 2359 PSI
- Max Bend Radius 2.25 inches

Item #	Description
A	
CXSCHD100	100' Single Bulk HD Coax, Black
CXSCHD250	250' Single Bulk HD Coax, Black
CXSCHD500	500' Single Bulk HD Coax, Black
CXSCHD1000	1000' Spool of Bulk HD Coax, Black
B	CXSCHD250R 250' Single Bulk Red HD Coax
C	CXSCHD250G 250' Single Bulk Green HD Coax
D	CXSCHD250B 250' Single Bulk Blue HD Coax
E	CXSCHD250W 250' Single Bulk White HD Coax

