

uplink® 4530EX








(888) 9-UPLINK | (888) 987-5465
www.uplink.com
sales@uplink.com



4G PRIMARY CELLULAR ALARM COMMUNICATOR

The Uplink® 4530EX is a true 4G (HSPA+) alarm communicator that features both Dial-Capture for full-event reporting and Siren/Bell Sampling for summary-event reporting. The combination of these features in a single communicator makes the 4530EX universally compatible with almost every alarm system and central station. Compatible with 2G, 3G and 4G cellular networks, the Uplink 4530EX communicates to central stations by dialup to any industry standard receiver, or over the internet to an IP receiver—all with the exceptional service and features you've come to expect from Uplink, the leading supplier of alarm communications.

KEY FEATURES:

-  Primary 4G Cellular communications, full alarm or summary event reporting
-  Power from the panel or separate 12V DC power supply
-  Installs in minutes with complete end-to-end signal verification
-  Contact ID, SIA, Modem IIe/IIIa/IIIa², or Pulse 4/2 (:10, :20, or :40 PPS)
-  Smart siren bell sampling to detect burglary or fire condition
-  Supports Uplink Remote
-  Eligible for Uplink Lifetime Guarantee



**SUPPORTS
UPLINK REMOTE
FOR INTERACTIVE
CONTROL**



UPLINK 4530EX DEVICE FEATURES:

- ✓ 4G technology for compatibility with 2G, 3G and 4G cellular networks
- ✓ Perfect for Primary communications for residential alarm systems
- ✓ Dial-Capture and Siren/Bell Sampling in a single unit.
- ✓ “Out-of-the-box” operation - no special programmer or receivers are required
- ✓ Remote on-demand testing for status and signal strength
- ✓ Live technical and activation support 8:00 a.m. to 8:00 p.m. EST, Monday through Friday
- ✓ Flat-rate billing for improved dealer profitability
- ✓ Supports Uplink Remote on systems with a keyswitch zone.

uplink® 4530EX

(888) 9-UPLINK | (888) 987-5465
www.uplink.com
sales@uplink.com

A TRUSTED PARTNER

The Uplink 4530EX is a new member of the Uplink family of alarm communicators. Our products deliver the unique combination of technology, quality, options and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996. Uplink options include 4G, 2G, CDMA or broadband communicators, primary or backup units, signaling only or Uplink Remote services, one year warranty or optional Lifetime Guarantee, summary or full event reporting, service in the U.S. or Canada, and different power choices to fit the needs of each installation. With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink has the experience and expertise to provide the most reliable products and the finest support.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and an advanced dealer web management tool.

For more information, visit the Uplink website and sign up to become an Uplink dealer at www.uplink.com.



UPLINK 4530EX 4G PRIMARY CELLULAR ALARM COMMUNICATOR

DIAL-CAPTURE &
SMART-SIREN SAMPLING

INTERACTIVE SERVICES	
Uplink Remote Service	Provides remote arming, arm status, event history by web browser or Smart-phone Apps. Multi-user support and event notifications by text message, email and smart-phone apps. Requires a momentary or maintained keyswitch zone.
INPUTS	
Dial-Capture	Full event reporting of Contact ID, SIA, Modem IIe/IIIa/IIIa2, or Pulse 4/2 (:10, :20, or :40 PPS) Internet or Dialup
Siren/Bell-Sampling	Connect to Siren/Bell (distinguishes between Burg/ steady and Fire/pulsed), or programmable to 12 volts
OUTPUTS AND REPORTING	
Central Station	Contact ID, SIA, Modem IIe/IIIa/IIIa ² , or Pulse 4/2 (:10,:20, or :40 PPS), Internet or Dialup
One Relay Output	Configurable - normally closed. Connect to the panel for trouble reporting
Other Reporting Methods	Email and Text Message to the alarm company
Periodic Test Signaling	Monthly, Weekly, or Daily
Status LEDs	<ul style="list-style-type: none"> • Signal Strength • Power • Panel Hook Status • Trouble
POWER REQUIREMENTS	
Uses 12V DC (200 mA constant, 600 mA peak)	Uninterrupted Class 2 Power Supply, 600 mA minimum
CELLULAR RADIO	
4G (HSPA+)	Compatible with 2G, 3G and 4G GSM networks
DIMENSIONS	
Height/Width/Depth (inches)	4.75 x 3.3 x 1.3, Antenna 3.75