

Concord Two-Way Voice LCD Keypad

Keypad for use with Concord Systems



OVERVIEW

The Concord® Two-Way Voice LCD Keypad controls Concord 4 panels and provides integrated two-way voice operation with a central station operator. Messages indicating the current status of the system are displayed in a large and easy-to-see LCD window, and emergency keys are highlighted on the keypad for added safety and convenience.

Keypad can be used for installer/user programming of the Concord control panels and has the capability of displaying customized zone-naming text.

A built-in speaker emits sounds to indicate alarm, status, and when a button has been pressed. The swing-down door reveals the control keys and a label showing basic system operating commands. The door may be removed for quick access to buttons and applications where a black keypad is desired.

Specifications

Compatibility	Concord 4 and later
Electrical	
Voltage	12VDC nominal
Current	60mA typical, 110mA in alarm
Environmental	
Operating Temperature	32°F~120°F (0°C~49°C)
Humidity	85% max. (non-condensing)
Physical	
Dimensions (LxWxD)	5.3 x 6.0 x 0.9 in. (135 x 153 x 2mm)
Regulatory	
	UL (985 1023, 1610)
	cUL (S545, 1023, S304)

STANDARD FEATURES

- Easy to install, wires to Concord bus
- Large easy-to-read display
- Multi-color status indicator
- Integrated two-way voice
- Stand-alone panic keys
- Stand-alone arming keys
- White door/black front can blend with any décor

Ordering Information

600-1070-E	Concord Two-Way Voice LCD Keypad
------------	----------------------------------



interlogix.com

Specifications subject to change without notice.

© 2017 United Technologies Corporation.
All rights reserved.

All trademarks are the property of their respective owners.
Interlogix is part of UTC Climate, Controls & Security
a unit of United Technologies Corporation.

2017/08 (GSP-2182)