

HD-TVI Analog Turret Cameras

3MPx and 5MPx
Resolution Cameras



OVERVIEW

The TruVision® HD-TVI Turret Cameras from Interlogix deliver cost-effective surveillance with 3MPx or 5MPx resolution HD-TVI technology over existing coaxial cable. Ideal for new or existing projects, HD-TVI Turret Cameras include an adapter plate for ease of installation and a variety of TruVision mounts and accessories, helping users stay within budget constraints without compromising security needs.

With the ability to see in low-light conditions, HD-TVI Turret Cameras provide color images by day and black-and-white images in night-time applications; in conjunction with IR illumination.

These cameras are specifically designed for use with TruVision HD-TVI DVRs that support 3MPx or higher resolution HD-TVI cameras. There is no limitation for 3MPx resolution cameras (up to max channels). Support for 5MPx resolution is limited to specific BNC ports, based on the recorder. Refer to the TruVision HD-TVI recorder guidelines for more details. Please note that first generation TruVision HD-TVI DVRs will not support these cameras.

STANDARD FEATURES

Video

- 3MPx or 5MPx HD resolution options
- HD-TVI or 960H output, selectable on 3MPx models
- HD-TVI output on 5MPx models
- Fixed or motorized varifocal lens options
- HD-TVI technology for transmitting HD quality video over existing coax cable

Video Enhancements

- 3MPx models provide Wide Dynamic Range (WDR), 120dB
- 5MPx models provide Digital Wide Dynamic Range (DWDR)
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios





Installation and Environment

- IP66 Environmental rating for the 3MPx models
- IP67 Environmental rating for the 5MPx models
- Coax OSD control
- Cable protection/management
- Multiple mounting options
- Turret adapter mounting plate included

Warranty

- 3-year warranty

Specifications

	TVT-4401 TVT-2401	TVT-4402 TVT-2402	TVT-4403 TVT-2403	TVT-4404 TVT-2404	
					
Camera	Image Sensor	1/3" CMOS		5 MPx Progressive Scan CMOS	
	Standard	HD-TVI			
	Signal System	NTSC/PAL			
	Resolution	3MPx Analog		5MPx Analog	
	Effective Pixels	2052 (H) x 1536 (V)		2592 (H) x 1944 (V)	
	Selectable via OSD (using higher resolution DVR)			2560 (H) x 1944 (V) @ 12.5 fps or 1920 (H) x 1080 (V) @ 25/30 fps	
	Synchronization	Internal			
	Day/Night	Day/Night IR cut filter with auto switch			
	Wide Dynamic Range	> 120 dB		DWDR	
	Electronic Shutter	NTSC: 1/30 s to 1/50,000 s; PAL: 1/25 s to 1/50,000 s			
	Minimum Illumination	0.01 lux @ f1.2 (AGC On); 0 lux with IR			
	Digital S/N Ratio	> 62 dB			
	Lens	2.8mm fixed	2.8-12mm motorized VF	2.8mm fixed	2.8 - 12mm motorized
	IR Range	66 ft. (20m)	132 ft. (40m)	66 ft. (20m)	132 ft. (40m)
On Screen Display (OSD)	TruVision® Coax OSD control on TVI	TruVision Coax OSD control on TVI or OSD menu button	TruVision Coax OSD control on TVI	TruVision Coax OSD control on TVI or OSD menu button	
OSD Languages	English/Chinese				
Video Output	3MPx TVI or 960H Analog		5MPx or 1080P TVI (only selectable via OSD when connector to 5MPx TVI recorder)		
Video Connector	1 - 75W BNC				
Intelligence	Mirror, Defect pixel correction, Smart IR				
Electrical/Mechanical	Voltage Input	12VDC			
	Current	417 mA	550 mA	250mA	750mA
	Power Consumption	5W (Max.)	6W (Max.)	3W (Max.)	9W (Max.)
	Dimensions	5 x 3.85 in. (226.7 x 97.84mm)	5.35 x 4.65 in. (135.78 x 118.2mm)	5 x 3.85 in. (126.7 x 97.84mm)	5.35 x 4.65 in. (135.78 x 118.2mm)
	Weight	0.77 lbs. (350g)	1.57 lb. (750g)	0.77 lbs. (350g)	1.57 lb. (750g)
Environmental	Operating Temperature (cold start)	-40°F~-140°F (-40°C~-60°C), Humidity <90% (non-condensing)			
	Environmental Rating	IP66		IP67	
Regulation	Compliance	FCC, CE, UL, WEEE, RoHS, REACH			

Important Notes: There are restrictions/rules when using HD-TVI 5MPx cameras with TruVision TVI recorders:


- The HD-TVI 5MPx cameras only work with the higher resolution HD-TVI recorders (TVR15HD or TVR45HD, or higher), firmware version 1.1 (or higher)
- There is a maximum number of HD-TVI 5MPx cameras that are supported per TruVision HD-TVI recorder
- The HD-TVI 5MPx cameras are only supported on specific ports of the TruVision HD-TVI Recorders

Guidelines:


- The TVR15HD Four Channel recorder, (FW v1.1 or higher) – supports a maximum of one HD-TVI 5MPx camera on BNC port 1.
- The TVR15HD/TVR45HD Eight Channel recorders, (FW v1.1 or higher) – supports up to two HD-TVI 5MPx cameras on BNC ports 1 and 2.
- The TVR15HD/TVR45HD Sixteen Channel recorders, (FW v1.1 or higher) – supports up to four HD-TVI 5MPx cameras on BNC ports 1, 2, 3 and 4.

Dimensional Diagrams

TVT-4401, TVT-2401, TVT-4403, TVT-2403 Fixed Turret Camera (adapter plate included)



TVT-4402, TVT-2402, TVT-4404, TVT-2404 Motorized Varifocal Turret Camera (adapter plate included)



HD-TVI Analog Turret Cameras

3MPx and 5MPx Resolution Cameras

Ordering Information

NTSC

TVT-4401	TruVision® HD-TVI Analog Turret Camera, 3MPx (use with 3MPx or higher TVI Recorders), 2.8mm Lens, True D/N, WDR, 20m IR, Dual-Output 960H Monitor or HD-TVI, Coax OSD control, 12VDC, IP66, NTSC
TVT-4402	TruVision HD-TVI Analog Turret Camera, 3MPx (use with 3MPx or higher TVI Recorders), 2.8~12mm Motorized Lens, True D/N, WDR, 40m IR, Dual Output 960H Monitor or HD-TVI, Coax & Button OSD Control, 12VDC, IP66, NTSC
TVT-4403	TruVision HD-TVI Analog Turret Camera, 5MPx (used w/5MPx or higher TVI recorders), 2.8mm lens, true D/N, DWDR, 20M IR, HD-TVI Output, Coax OSD control, 12VDC, IP67, NTSC
TVT-4404	TruVision HD-TVI Analog Turret Camera, 5MPx (used w/5MPx or higher TVI recorders), 2.8~12mm motorized lens, true D/N, DWDR, 40M IR, HD-TVI Output, Coax & button OSD control, 12VDC, IP67, NTSC

PAL

TVT-2401	TruVision® HD-TVI Analog Turret Camera, 3MPx (use with 3MPx or higher TVI Recorders), 2.8mm Lens, True D/N, WDR, 20m IR, Dual-Output 960H Monitor or HD-TVI, Coax OSD control, 12VDC, IP66, PAL
TVT-2402	TruVision HD-TVI Analog Turret Camera, 3MPx (use with 3MPx or higher TVI Recorders), 2.8~12mm Motorized Lens, True D/N, WDR, 40m IR, Dual Output 960H Monitor or HD-TVI, Coax & Button OSD Control, 12VDC, IP66, PAL
TVT-2403	TruVision HD-TVI Analog Turret Camera, 5MPx (used w/5MPx or higher TVI recorders), 2.8mm lens, true D/N, DWDR, 20M IR, HD-TVI Output, Coax OSD control, 12VDC, IP67, PAL
TVT-2404	TruVision HD-TVI Analog Turret Camera, 5MPx (used w/5MPx or higher TVI recorders), 2.8~12mm motorized lens, true D/N, DWDR, 40M IR, HD-TVI Output, Coax & button OSD control, 12VDC, IP67, PAL

Accessories

For TVT-4401/TVT-2401 or TVT-4402/TVT-2402 or TVT-4403/TVT-2403 or TVT-4404/TVT-2404

TVD-BB3	TruVision Dome Back Box
TVD-BB3A	TruVision Angled Back Box
TVD-M2-WM	TruVision Wall Mount
TVB-CB3	TruVision 3 Inch Cup Base (use w/TVD-SNB, TVD-PPB)
TVD-SNB	TruVision Swan Neck Bracket
TVD-SNB-BB	TruVision TVD-SNB Back Box, 4 directional Conduit
TVD-M-CMA	TruVision Corner Mount Adapter
TVD-M-PMA	TruVision Pole Mount Adapter
TVD-PPB	TruVision Dome Pendant Mount Bracket



interlogix.com

Specifications subject to change without notice.

© 2017 United Technologies Corporation.
All rights reserved.

All trademarks are the property of their respective owners.
Interlogix is part of UTC Climate, Controls & Security,
a unit of United Technologies Corporation.

2017/08 88471