

## DS-2CE57D3T-VPITF

### 2 MP Outdoor Ultra-Low Light Dome Camera



- 2 MP High Performance CMOS
- Up to 1080p Resolution
- Ultra-Low Light
- 2.8 mm, 3.6 mm, and 6 mm fixed lens options
- EXIR 2.0 up to 100 ft (30 m) IR Range
- Smart IR
- 120dB True WDR, 3D DNR
- Multiprotocol Output: TVI/AHD/CVI/ CVBS
- Up-the-Coax (HIKVISION-C)
- IP67, IK10 Protection

The Hikvision DS-2CE57D3T-VPITF 2 MP Outdoor Ultra-Low Light Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 100 feet (30 meters).

The 2.8 mm, 3.6 mm, and 6 mm fixed lens options are optimized for viewing angles that fit any situation. True 120db WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

**Available models:**  
DS-2CE57D3T-VPITF



# Specifications

## DS-2CE57D3T-VPITF

### Camera

Image Sensor	2.0 megapixel progressive scan CMOS
Signal System	NTSC
Video Frame Rate	1080p @ 30 fps
Resolution	1920 (H) × 1080 (V)
Minimum Illumination	Color: 0.005 lux @ (f/1.2, AGC on), 0 lux with IR
Shutter Speed	1/30 s to 1/50,000s
Lens	2.8 mm, 3.6 mm, and 6 mm fixed lens options
Horizontal Field of View	106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)
Lens Mount	M12
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 340°, tilt: 0° to 75°, rotate: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	>120 dB

### Menu

AGC	High/medium/low
D/N Mode	Auto/color/BW (black and white)
Image Mode	Standard/high-sat
BLC (Backlight Compensation)	Yes
WDR	Yes
3D DNR	Level 1 to 9
Language	English
Functions	Brightness, sharpness, 3D DNR, mirror, smart IR







### Interface

Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS

### General

Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 20%
Power Consumption	Maximum 4.6 W
Ingress Protection	IP67, IK10
Material	Metal
IR Range	Up to 100 ft (30 m)
Dimensions	Ø4.4" × 3.2" (Ø111 mm × 82.4 mm)
Weight	Approximately 1.07 lbs (487 g)

# Accessories

					
<b>WMS + PC110</b> Wall Mount Short + 110 mm Pendant Cap	<b>CB110</b> Conduit Base	<b>AB110</b> Angled Base	<b>CPM + PC110</b> Ceiling Pendant Mount + 110 mm Pendant Cap	<b>WM110</b> Plastic Wall Mount	<b>PM</b> Pole Mount

# Dimensions

