



The wireless CO detector features an onboard sounder, a CO sensor, LED indicators and local test capability to allow the user total visibility of its functionality. It is self-monitoring, alerting the user when sensor maintenance is needed or batteries are low and automatically supervising the radio link.

### Product Features

---

Local test and silence alarm functions

---

Low battery detection

---

Maintenance warning

---

Tamper switch for prevention against sensor removal

---

Ten year CO sensor life

### Product Specifications

---

Dimensions: 5.3" x 2.3"

---

Weight: 7.0 oz. without battery

---

Internal battery type: One Panasonic CR123A

---

Typical battery life: 3-5 years

---

Low battery threshold: Low battery signal at 2.7V

---

Operating environment:

---

Temperature: 32°F to 122°F (-0°C to 50°C)

---

Humidity: 0 to 95%, non-condensing

---

Market: North America

---

EchoStream® frequency: 902-928 MHz, frequency hopping spread spectrum

---

Regulatory compliance: FCC, Industry Canada, AS/NZS 4268:2012, CSFM, NPFA 720, UL2034, UL2075

---

Check-in time frequency: 3 minutes

---

Sounder:

---

Alarm: 85 dB @ 3 m, temporal output

---

Low battery: 1 chirp every 45 seconds

## Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

EN1245 Family Wireless CO Detector Installation Instructions

---

EchoStream Developer Guide

---

Inovonics Product Catalog: North America

---

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.