



Summary


The VMAX[®] IP G4[™] is an NDA and TAA compliant, easy to use embedded PoE network video recorder (NVR) that allows you to go from power up to monitoring in minutes! Available with 4 Power over Ethernet (PoE) ports and expandable to 9 cameras, the NVRs can record and manage single-sensor IP cameras up to 4K resolution and comes with up to 16TB internal storage.

Features

- Complete installation, setup and camera configuration in minutes!
- CCIP[™] system encryption via TLS protects your surveillance system from out of network attacks
- Record and manage single-sensor IP cameras at real-time 30fps up to 4K (3840x2160), with 40Mbps maximum throughput
- Local power for up to 4 IP cameras via resident PoE switch
- DW Witness[™] turns a smartphone or tablet into a surveillance camera
- PathFinder[™] easy end-to-end remote connection with NAT Traversal (STUN/TURN) support
- Automatic device discovery
- Compatible with ONVIF cameras
- 0-16TB storage options
- Transfer real-time data using Real Time Streaming Protocol (RTSP)
- Snapshot Notify[™]: Interval camera image verification sent to an email
- Remote management with C3[™] CMS for Windows[®] and Mac[®]
- Event camera group recording
- System analysis with real-time system, PoE and network status monitoring
- Event notifications via email, text and C3[™] CMS and push notifications to mobile devices
- Mobile Application for iOS[®] and Android[®] devices
- Dual-stream recording
- Easy drag and drop camera management
- Instant backup during playback
- True HD and VGA simultaneous output support
- Compatible with DW[®] Spot[™] Monitoring module for Public View Monitors
- 1 audio input, 1 audio output
- 4 sensor inputs, 1 relay output
- Advanced H.265/H.264 Linux embedded NVR
- NVR calculation and auto-recording configuration
- Screen saver to protect monitor screen
- Import/export configuration between multiple NVRs
- Auto or manual firmware upgrade available
- NDA/TAA compliant
- 5 year limited warranty

Dimensions

Unit: Inch (mm)



Specifications

VIDEO		
Operating system	Embedded Linux [®]	
System	Channel	9 channel
	No. of PoE	4 Ch
	Max supported resolution	IP camera max. 4K (3840x2160)
	Communication protocol	ONVIF [™] profile S
Display	PoE type	100Mbps, 802.3at
	Speed	270fps
	Screen mode	1, 4 and 9
Video out	Monitor	True HD and VGA
	Resolution	3840x2160 (4K), 1920x1080, 1280x1024, 1024x768
System operation	USB mouse, PTZ control by keyboard (optional)	
PERFORMANCE		
Recording speed	Up to 270fps up to 4K (2160p) resolution	
Max. throughput	40 Mbps	
Recording streaming	Dual-stream	
Recording modes		Continuous, scheduled, sensor and motion detection recording
		Pre- and post-alarm recording, emergency recording, quick backup
Playback and search	Speed	x1, x2, x4, x8, x16, x32, x64, x99
	Channel and resolution	1 and 4 main-stream, 9 & 16: sub-stream
	Function	Timeline, calendar (date and time), event search, thumbnail search, smart motion search
Audio input / output	1Ch input / 1Ch output	
Alarm input / relay output	4Ch inputs / 1Ch output	
PTZ control	RS-485, ONVIF	
Storage	HDD interface	1x SATA HDD
	Max. internal storage	Up to 16TB
	HDD healthcheck	Temperature, S.M.A.R.T. with email notifications Real-time temp alert
Transaction verification	Text-in Based (USB to Serial support, TCP/IP Network), Display POS Data on Live & Playback	
NETWORK		
LAN	1000Mbps Ethernet (RJ45)	
Protocols	IPv4, TCP/IP, DHCP, HTTP, RTSP, STMP, FTP, Zero Configuration, NTP, DDNS	
Access	Web viewer	Live, playback and configuration, up to 10 connections
	Video streaming functions	Dual recording for live and playback and dual stream for local recording and network transmission
	Monitoring software	PathFinder [™] easy end-to-end remote connection C3 [™] CMS, DW Mobile Plus [™]
Network functions	Live monitoring, remote playback and file backup	
Remote system control	Remote system reboot, system management, notifications and remote PTZ control	
Remote Time sync	Time synchronization to an NTP server (pool.ntp.org)	
Remote system notifications	Notifications for system health, events and alarms	
System recovery after power failure	Auto-reboot and journaling file system	
Other function	Firmware upgrade	FTP, USB and CMS over Network
	Back-up	Local backup by USB, network backup by CMS Import and export settings, watermark and AVI file backup
	Special features	Snapshot Notify [™] : Interval camera image verification Event and push notifications via email, text and C3 [™] Digital Zoom in live and playback POS text-in based (USB to serial support, TCP/IP network)
	Mobile client	DW Mobile Plus app for Apple [®] and Android [®] devices DW Witness [™] turns a smartphone or tablet into a surveillance camera
Health check	Real-time system, network and PoE status monitoring	
GENERAL		
Operating temperature and humidity	32-113 °F (0-45 °C) / 10-90% RH	
Certification	CE, FCC, KCC, NDA, TAA	
System	Power requirement	48V DC, 1.25A
	Power consumption	60W (recorder + PoE ports)
	Max power per port	802.3at POE+ (Class4), up to 30W per port
PoE	Total PoE power budget	48W
Dimension (W x D x H)	11.81" x 9.8" x 1.77" (300 x 249 x 45 mm)	
Warranty	5 year limited	



Increase sales and profitability. Sign up and become a DW Channel Partner today!



☎ : 866.446.3595 ✉ : sales@digital-watchdog.com 🌐 : www.digital-watchdog.com



Available Models

- DW-VG494P - no HDD.
- DW-VG492T4P - 2TB internal storage.
- DW-VG494T4P - 4TB internal storage.
- DW-VG496T4P - 6TB internal storage.
- DW-VG498T4P - 8TB internal storage.
- DW-VG4910T4P - 10TB internal storage.
- DW-VG49124P - 12TB internal storage.
- DW-VG4916T4P - 16TB internal storage.



Increase sales and profitability. Sign up and become a DW Channel Partner today!



☎: 866.446.3595 ✉: sales@digital-watchdog.com 🌐: www.digital-watchdog.com

