

Video Doorbell Data Sheet

ADC-VDB750

www.alarm.com

© 2022 Alarm.com. All rights reserved, 221104



Recording compression: H.264

Ingress protection: IP65

Max resolution: 1440×1440

Image sensor: 1/2.4", 2.36 MP, HDR

Lens / angle of view: 165° horizontal, 145° vertical

Low-light sensitivity: O lux with IR

IR range: Up to 15 feet (5 meters)

Image adjustments: Flip, brightness, contrast, saturation, sharpness, exposure

Wireless connectivity: 802.11 b/g/n/ac, 2.4 & 5 GHz

Operating temperature: -58°F - 122°F

Operating humidity: < 95% (noncondensing) RH

Dimensions: (W x L x D) 1.5 x 4.81 x 1.18" assembled with back plate (38 x 122 x 30 mm)

Activity Detection: Advanced Video Analytics for People Detection

Audio: Two-Way Audio (Full Duplex)

Power requirements: AC: 16-24 VAC, 10-40VA (16VAC, 10VA recommended) DC: 15-24 V, 6-20W





Overview

Introducing the latest addition to Alarm.com's family of video doorbells the ADC-VDB750. This doorbell offers crystal clear 2MP picture and an expansive 165° horizontal and 145° vertical Field of View so customers can see and do more at the front door. Alarm.com's powerful People Detection and crisp Two-Way Audio help reduce false notifications while bringing increased awareness and allowing users to communicate with visitors. Plus a wide range of operating temperatures increase install flexibility making this a great choice in any environment.

Features

- Expansive 165° horizontal and 145° vertical Field of View ensures customers get a full picture of what's happening at their
- Video Analytics with rapid People Detection for faster, more relevant alerts and fewer false notifications
- Full HD resolution, High Dynamic Range (HDR), and infrared night vision
- Two-Way Audio
- Compatible with the Alarm.com Smart Chime (W115C)
- 2MP live video and saved clip viewing via the app and customer website
- Dual antenna (2x2 MIMO) Wi-Fi for improved range (2.4 GHz and 5 GHz)

Included accessories

- ADC-VDB750 video doorbell
- ADC-VDB750 wallplate (with pre-assembled set screw and wire terminal screws)
- Wall anchors (x2) & screws (x2)

Status light guide

Off: Power off • • • • • • • • • •

Blinking yellow: Camera power cycling

Solid red: No local or Intenet connection

Blinking red: Power on, camera booting

• • • • • • • • • • Alternating red and green: Camera resetting to factory default

Solid green: Connected to Alarm.com

•••••• Blinking green: Local network connection

Blinking blue: WPS mode

.

Blinking white: Wi-Fi Access Point mode