


OPTEX Visual Verification Bridge

For Professionally
Monitored Security
Systems

Model:
CKB-312V2



What The Central Station Sees
Delivered in 5 seconds



What An End-User Sees
Only when/if criminal intent is detected



Intelligent Visual Monitoring Solution

The OPTEX Visual Verification Bridge series features powerful next generation gateway devices that allows security professionals to connect ONVIF compatible cameras and alarm sensors to the Cloud-based Visual Verification Portal powered by CHEKT.

Aimed primarily to monitored alarm systems, the solution provides central station operators the ability to visually verify alarm threats within seconds, and respond accordingly. When designed, installed, and maintained properly, this system can eliminate 100% of false dispatches and dramatically increase customer satisfaction and retention. The solution allows the operator to share video alarm events with the site emergency contacts to validate or dismiss the alarm.

The Bridge CKB-312V2 (12 version 2.0 channel model) allows the integrator to pair multiple cameras with sensors for visual verification of events, simplifying the installation for small to larger sites using a single device to transmit up to twelve event-driven ONVIF camera feeds. Installing the Bridge as an alarm panel module is a cost-effective way to add visual verification to existing intrusion systems, using legacy equipment.

In addition, a smart-phone App is available, allowing end users the option to have a professionally installed and self-monitored visual verification solution.



Affordable & Effective — Visual Verification Made Easy

- Compatible with any ONVIF S compliant device
- Allows pairing of traditional alarm zones to cameras
- Supports HD over coax camera/DVR (supports DVR)
- Line level output source for talk-down capability

For Central Stations

- No set-up cost/integration with CS
- 5 second average delivery time to CS
- Pre and post-alarm event visual verification
- Does not require Flash video player



Integrates With All Central Station Automation Systems.

For End Users

- 5 second average delivery time to CS
- Low cost of ownership
- SMS text notification
- Secure video from protected premise to CS (SSL)

For Dealers

- 30 minute installation time
- No firewall configuration
- Intuitive UI mapping
- Powered by PoE
- DVR/NVR port-forwarding not required
- Camera port-forwarding not required
- Works with any alarm panel
- Works without an alarm panel
- Works with any ONVIF S compliant device
- Compatible with cameras with EDGE analytics
- IP Communicator
- Does not require SMTP setup on devices (DVR/NVR/Cameras)





Specifications

Model	CKB-312V2	Video analytics support	ONVIF Event Messaging Protocol
Digital alarm inputs	12 x Digital Input Zones	Event triggers	Zone Input Triggers, ONVIF Event Topics, AI Event Triggers with API
Relay output	4 x Relay Output (NO/NC) – 5Amps @24v DC	Alarm events	Transmitted via IP to Central Station Automations
SD card slot	microSD/SDHC card slot (Used only for internal Bridge OS – Bridge Warranty Voided if Removed!)	Audio in	Available on supported cameras with audio in the video stream
Audio output	1/8" (3.5mm) Line Level Output (non-amplified)	Ethernet	RJ-45 10/100/BASE-T Connection
Reset button	Bridge factory reset	Encryption/security	TLS/SSL (Secure Socket Layer)
USB ports	2 x USB2.0 type A + 2 x USB3.0 type A	Operating temp/humidity	0C ~ +40°C (32°F ~ 85°F) / Less than 85% RH
STA (status)	Bridge Power – On (Armed Status – Red[Armed] Green[Disarmed])	Bridge power source	12v DC / PoE IEEE 802.3af class4
Network	Network Connection Indicator	Power consumption	DC : 800mAmps Peak PoE : 10.5W Peak
DI (alarm 1-8 or alarm 1-12)	Digital Input Indicators (Red – Alarm, Off – Normal)	Digital input zones	Input Voltage Range: 0-12v DC (All Ground Termals Are Common)
Video source recommendations	IP devices with available RTSP Stream. Video Source Requirements:~ D1 Resolution: 720x480 & 6 FPS	Relay output	max 5Amps @24v DC
Video compression support	H.264	Arming input	Input Voltage Range: 0-12v DC (All Ground Termals Are Common) – 1.87v ADC Reading with no external Connection
Video authentication support	ONVIF, RTSP, HTTP, CheKT API	Color/material	White / Polycarbonate (PC)
Video transmission security	TLS/SSL Encryption to Cloud & Central Station	Product dimensions/weight	225mm x 96mm x 35mm (8.9" x 3.78" x 1.38"), Weight : 350g (0.8lb)

Dimensions

Unit: mm

CKB-312V2



800.966.7839

www.optexamerica.com
sales@optexamerica.com

224.442.4358

www.chekt.com
customercare@chekt.com

