



ENVIROALERT PROFESSIONAL® -ULTRA-LOW SENSOR

Model Number: *EAPro-ULS* (RTD-PT1000 SENSOR)
-148 to +257 °F (-100 to +125 °C)



EAPro-ULS is a stainless-steel temperature sensor accessory for:

- EnviroAlert Professional® Gateway (*EAPro-GTWY*)
- EnviroAlert Professional® Multi-Function Transmitter (*EAPro-WMFT*)

Features:

- PT1000 sensor (sensor is a 2 wire connection)
- Stainless steel thermistor sensor
- Sturdy stainless-steel housing
- Maximum cable run of 1,000' (304.8m) [18-22 AWG twisted pair]
- Consider Winland accessories:
 - Temp-G-B (Glycerin Bottle)
 - Temp-S-K (Splice Kit)
 - Temp-B-T (Buffer Tube)

Specifications:

Sensor Length	2.95" (7.5cm)
Sensor Diameter	0.25" (6.35mm)
Cable Lead	10' (3.05m) [extend up to 1,000' (304.8m) using 18-22 AWG twisted pair]
Weight	0.80oz (22.68g)
Temperature Range	-148 to +257 °F (-100 to +125 °C) w/accuracy ±3.6 °F (±2.0 °C)

