

# **SK-MONITOR**

# Intelligent Monitor Module

The SK-MONITOR is an addressable monitor module for use with Honeywell Silent Knight Series fire alarm control panels (FACPs). The SK-MONITOR is intended for use in intelligent, two-wire systems, where individual address of each module is selected using the built-in rotary switches.

The SK-MONITOR supports Class A supervised or Class B supervised wiring to the load device. Conventional 4-wire smoke detectors can be monitored for alarm and trouble conditions.

#### **INSTALLATION**

The SK-MONITOR mounts directly into a 4" square electrical box. The box must have a minimum depth of 2-1/8". A surface mount electrical box (System Sensor® PN SMB500) is available from Silent Knight.



SK-MONITOR

## FEATURES & BENEFITS

- Single contact monitor Panel controlled
- Support for Class A and Class B wiring
- Fully supervised
- Panel controlled status LED that flashes green in normal state and is solid red in alarm
- SEMS screws for easy wiring
- UL Listed
- Rotary address switches for fast installation

# SK-MONITOR Technical Specifications

#### **PHYSICAL**

**Height:** 4.5" H x 4" W x 1.25" D (11.4 X 10.2 X 3cm) **Shipping Weight:** 6.3 oz (196 g)

#### **ELECTRICAL**

Operating Voltage: 15-32VDC Current Draw (LED on): 5.0mA max Operating Current (LED flashing):  $375\mu$ A Standby Current:  $400\mu$ A max @ 24 VDC (one communication every 5 sec with 47K EOL);  $550\mu$ A max @ 24 VDC (one communication every 5 sec with EOL <1K)

5.5 mA (with LED latched on)

LED Current: 5.5 mA (with LED latched on)

End-of-Line Resistance:  $47 \,\mathrm{K}\,\Omega$ 

Initiating Device Circuit Wiring Resistance: 1,500

 $\Omega$  max

SLC Loop Resistance:  $40 \Omega$  max.

#### ENVIRONMENTAL

Operating Temperature:  $32^{\circ}F - 120^{\circ}F$  ( $0^{\circ}C - 120^{\circ}F$ )

49°C)

Humidity: 10% - 93% non-condensing

#### ORDERING INFORMATION

SK-MONITOR: Monitor Module

#### ACCESSORIES.

SMB500: 4" Square surface mount electrical box

#### **COMPATIBILITY**

The SK-MONITOR is compatible with the following Honeywell Silent Knight fire alarm control panels:

6820: Addressable fire alarm control panel
6820EVS: Addressable fire alarm control panel
with an emergency mass notification system.
6808: Addressable fire alarm control panel
6700: Addressable fire alarm control panel
5700: Addressable fire alarm control panel
5808: Addressable fire alarm control panel
5820XL: Addressable fire alarm control panel
5820XL-EVS: Addressable fire alarm control panel
with an emergency mass notification system

For a complete listing of all compliance approvals and certifications, please visit www.silentknight.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Silent Knight®, System Sensor® and Honeywell® are registered trademarks of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, call 800-446-6444.

### For more information

Learn more about Honeywell Silent Knight and other products by visiting www.silentknight.com

#### Honeywell Silent Knight

12 Clintonville Road Northford, CT 06472 800-328-0103

