

Recessed Door/Window Sensor

TX-E Series



OVERVIEW

The TX-E Series Recessed Door/Window Sensor from Interlogix is compact and robust for dependable operation. Hidden within the door frame, this contact is virtually invisible when the door is closed making it ideal when discreet sensors are needed. The TX-E Series Recessed Door/Window Sensor uses a replaceable lithium battery that lasts up to five years under normal usage and comes with a standard flanged top.

STANDARD FEATURES

- Field proven wireless technology
- Compact design
- Easy replaceable battery
- Wide gap — up to 1" maximum
- Replaceable battery with up to 5 years of battery life (based on usage)
- 2 year warranty

Specifications

Compatibility	Interlogix Learn-Mode panels and receivers
Frequency	319MHz (Crystal based)
Battery	CR2
Battery Life	5 years, typical
Operating Temperature	32°F (0°C) to 120°F (49°C)
Operating Humidity	5-95% non condensing
Weight	1.4 oz.
Sensor Dimensions (WxH)	.75 x 2.5 in. (1.905 x 6.35 cm)
Magnet Dimensions (WxH)	.75 x 0.5 in. (1.905 x 1.27 cm)
Color	White
Magnet type	N48 rare earth
Magnet gap	1 in. maximum
Approvals	FCC/IC

Ordering Information

TX-E221	Recessed Door/Window Sensor
----------------	-----------------------------

interlogix.com

Specifications subject to change without notice.

© 2016 United Technologies Corporation.
All rights reserved.

All trademarks are the property of their respective owners.
Interlogix is part of UTC Climate, Controls & Security
a unit of United Technologies Corporation.

2016/05 (LI-1705)